

Package ‘MeLSI’

May 26, 2026

Type Package

Title Metric Learning for Statistical Inference in Microbiome Analysis

Version 1.0.0

Description MeLSI (Metric Learning for Statistical Inference) is a novel machine learning method for microbiome data analysis that learns optimal distance metrics to improve statistical power in detecting group differences. Unlike traditional distance metrics (Bray-Curtis, Euclidean, Jaccard), MeLSI adapts to the specific characteristics of your dataset to maximize separation between groups. The method uses an ensemble of weak learners to identify which microbial features drive group differences, providing both improved statistical power and biological interpretability through feature importance weights.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 4.5.0)

URL <https://github.com/NathanBresette/MeLSI>

BugReports <https://github.com/NathanBresette/MeLSI/issues>

Imports vegan, ggplot2, phyloseq, stats, utils

Suggests testthat, knitr, rmarkdown, BiocManager, BiocStyle,
BiocParallel, Matrix, microbiome

VignetteBuilder knitr

biocViews Software, StatisticalMethod, Microbiome

git_url <https://git.bioconductor.org/packages/MeLSI>

git_branch RELEASE_3_23

git_last_commit ce5c7ee

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-05-25

Author Nathan Bressette [aut, cre] (ORCID: <https://orcid.org/0009-0003-1554-6006>),
 Aaron C. Ericsson [aut] (ORCID: <https://orcid.org/0000-0002-3053-7269>),
 Carter Woods [aut] (ORCID: <https://orcid.org/0009-0007-5345-2712>),
 Ai-Ling Lin [aut, fnd] (ORCID: <https://orcid.org/0000-0002-5197-2219>)

Maintainer Nathan Bressette <nathanbressette04@gmail.com>

Contents

clr_transform	2
generate_test_data	3
melsi	4
plot_feature_importance	5
plot_pcoa	6
plot_vip	7

Index	8
--------------	----------

clr_transform	<i>CLR Transformation for Microbiome Data</i>
---------------	---

Description

Applies centered log-ratio (CLR) transformation to microbiome count data. This transformation is recommended for microbiome data before running MeLSI.

Usage

```
clr_transform(X, pseudocount = 1)
```

Arguments

X	Feature matrix (samples x taxa) with raw counts or relative abundances
pseudocount	Small constant to add before log transformation (default: 1)

Value

CLR-transformed matrix with preserved column names

Examples

```
# Generate synthetic data
test_data <- generate_test_data(n_samples = 20, n_taxa = 30, n_signal_taxa = 5)
X <- test_data$counts

# Transform microbiome data
X_clr <- clr_transform(X)
```

```
# Verify transformation
stopifnot(is.matrix(X_clr))
stopifnot(nrow(X_clr) == nrow(X))
```

generate_test_data *Generate Synthetic Microbiome Data for Testing*

Description

Creates synthetic microbiome count data with specified characteristics for testing and demonstration purposes.

Usage

```
generate_test_data(
  n_samples = 60,
  n_taxa = 100,
  n_signal_taxa = 10,
  effect_size = 2,
  group_balance = 0.5
)
```

Arguments

n_samples	Total number of samples to generate
n_taxa	Total number of taxa (features)
n_signal_taxa	Number of taxa with differential abundance between groups
effect_size	Magnitude of differential effect (fold-change)
group_balance	Proportion of samples in group A (default 0.5 for balanced)

Value

A list containing:

- counts: Matrix of count data (samples x taxa)
- metadata: Data frame with sample metadata including Group
- signal_taxa: Vector of indices for taxa with true differential abundance

Examples

```
# Generate balanced dataset with 60 samples and 100 taxa
test_data <- generate_test_data(n_samples = 60, n_taxa = 100, n_signal_taxa = 10)
X <- test_data$counts
y <- test_data$metadata$Group
```

melsi

Run MeLSI Analysis

Description

Performs MeLSI (Metric Learning for Statistical Inference) analysis for microbiome data. Automatically handles both pairwise comparisons (2 groups) and multi-group analysis (3+ groups).

Usage

```
melsi(
  X,
  y,
  analysis_type = "auto",
  n_perms = 200,
  B = 30,
  m_frac = 0.8,
  show_progress = TRUE,
  plot_vip = TRUE,
  correction_method = "BH",
  BPPARAM = NULL
)
```

Arguments

X	A matrix of feature abundances with samples as rows and features as columns
y	A vector of group labels for each sample
analysis_type	Type of analysis to perform: - "auto" (default): Automatically choose based on number of groups - "pairwise": For 2 groups or all pairwise comparisons for 3+ groups - "omnibus": Global analysis for 3+ groups (requires at least 3 groups) - "both": Both omnibus and pairwise for 3+ groups
n_perms	Number of permutations for p-value calculation (default: 200)
B	Number of weak learners in the ensemble (default: 30)
m_frac	Fraction of features to use in each weak learner (default: 0.8)
show_progress	Whether to display progress information (default: TRUE)
plot_vip	Whether to display Variable Importance Plot (default: TRUE)
correction_method	Multiple testing correction method for pairwise comparisons (default: "BH")
BPPARAM	A BiocParallelParam object specifying the parallel backend to use for permutation testing. If NULL (default), permutations run sequentially. Requires the BiocParallel package.

Value

For 2 groups or pairwise analysis: List with F-statistic, p-value, feature weights, etc. For 3+ groups: List containing omnibus results, pairwise results, or both.

Examples

```
# Generate test data
test_data <- generate_test_data(n_samples = 40, n_taxa = 50, n_signal_taxa = 5)
X <- test_data$counts
y <- test_data$metadata$Group

# CLR transformation
X_clr <- clr_transform(X)

# Run MeLSI analysis
results <- melsi(X_clr, y, n_perms = 19, B = 10, show_progress = FALSE)

# Check results
stopifnot(is.list(results))
stopifnot("F_observed" %in% names(results))
stopifnot("p_value" %in% names(results))
```

plot_feature_importance

Plot Feature Importance from MeLSI Analysis

Description

Creates a barplot showing the top features ranked by their learned weights

Usage

```
plot_feature_importance(
  feature_weights,
  top_n = 8,
  main_title = NULL,
  directionality = NULL
)
```

Arguments

feature_weights	Named vector of feature weights
top_n	Number of top features to display (default: 8)
main_title	Optional title for the plot
directionality	Optional named vector indicating which group has higher abundance for each feature

Value

A ggplot2 object (invisibly)

Examples

```
# Generate test data and run MeLSI
test_data <- generate_test_data(n_samples = 30, n_taxa = 20, n_signal_taxa = 5)
X <- test_data$counts
y <- test_data$metadata$Group
X_clr <- clr_transform(X)
results <- melsi(X_clr, y, n_perms = 19, B = 10, show_progress = FALSE)

# Plot feature importance
plot_feature_importance(results$feature_weights, top_n = 10)
```

plot_pcoa

Plot PCoA from MeLSI Results

Description

Creates a Principal Coordinates Analysis (PCoA) plot using the learned MeLSI distance matrix.

Usage

```
plot_pcoa(melsi_results, X, y, title = "PCoA using MeLSI Distance")
```

Arguments

melsi_results	Results object from melsi() function
X	Original feature matrix (samples x taxa)
y	Group labels vector
title	Optional custom title for the plot (default: "PCoA using MeLSI Distance")

Value

A ggplot2 object (invisibly)

Examples

```
# Generate test data and run MeLSI
test_data <- generate_test_data(n_samples = 30, n_taxa = 20, n_signal_taxa = 5)
X <- test_data$counts
y <- test_data$metadata$Group
X_clr <- clr_transform(X)
results <- melsi(X_clr, y, n_perms = 19, B = 10, show_progress = FALSE)

# Plot PCoA
plot_pcoa(results, X_clr, y)
```

`plot_vip`*Plot VIP from MeLSI Results (User-Friendly Wrapper)*

Description

Simplified function to plot Variable Importance (VIP) directly from MeLSI results. Automatically extracts feature weights and optionally includes directionality information.

Usage

```
plot_vip(melsi_results, top_n = 15, title = NULL, directionality = TRUE)
```

Arguments

`melsi_results` Results object from `melsi()` function
`top_n` Number of top features to display (default: 15)
`title` Optional custom title for the plot
`directionality` Whether to include directionality coloring (default: TRUE)

Value

A `ggplot2` object (invisibly)

Examples

```
# Generate test data and run MeLSI
test_data <- generate_test_data(n_samples = 30, n_taxa = 20, n_signal_taxa = 5)
X <- test_data$counts
y <- test_data$metadata$Group
X_clr <- clr_transform(X)
results <- melsi(X_clr, y, n_perms = 19, B = 10, show_progress = FALSE)

# Plot VIP with directionality (default)
plot_vip(results, top_n = 10)
```

Index

BiocParallelParam, [4](#)

clr_transform, [2](#)

generate_test_data, [3](#)

melsi, [4](#)

plot_feature_importance, [5](#)

plot_pcoa, [6](#)

plot_vip, [7](#)