Package 'leeBamViews'

May 26, 2026

Title leeBamViews -- multiple yeast RNAseq samples excerpted from Lee 2009

Version 1.48.0

Author VJ Carey <stvjc@channing.harvard.edu>

Description data from PMID 19096707; prototype for managing multiple NGS samples

Depends R (>= 2.15.0), Biobase, Rsamtools (>= 0.1.50), BSgenome

Imports GenomicRanges, GenomicAlignments, methods, S4Vectors, parallel, IRanges

Suggests biomaRt, org.Sc.sgd.db, edgeR

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic 2.0

LazyLoad yes

biocViews ExperimentData, Saccharomyces_cerevisiae_Data, SequencingData, RNASeqData, SNPData

RoxygenNote 7.1.2

git_url https://git.bioconductor.org/packages/leeBamViews

git_branch RELEASE_3_23

git_last_commit 9247797

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-05-26

Contents

bs1 2
leeRPKM 4
leeUnn 5
tabulateReads 6
totalReadCounts 7

Index **8**

bs1 *BamViews instance construction related to yeast RNA-seq*

Description

BamViews instance construction related to yeast RNA-seq

Format

The format is: Formal class 'BamViews' [package "Rsamtools"] with 5 slots
..@ bamPaths : chr [1:8] "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt5_13e.bam"
"/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt6_13e.bam" "/Users/stvjc/ExternalSoft/R-
devel/library/leeBamViews/bam/rlp5_13e.bam" "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/rlp6_13e.bam
...
..@ bamIndicies : chr [1:8] "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt5_13e.bam"
"/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt6_13e.bam" "/Users/stvjc/ExternalSoft/R-
devel/library/leeBamViews/bam/rlp5_13e.bam" "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/rlp6_13e.bam
...
..@ bamSamples :Formal class 'DataFrame' [package "IRanges"] with 6 slots
.. .. ..@ rownames : chr [1:8] "isowt.5" "isowt.6" "rlp.5" "rlp.6" ...
.. .. ..@ nrows : int 8
.. .. ..@ elementMetadata: NULL
.. .. ..@ elementType : chr "ANY
" .. .. ..@ metadata : list()
.. .. ..@ listData :List of 2
.. ..$ geno: chr [1:8] "isowt" "isowt" "rlp" "rlp" ...
.. ..$ lane: chr [1:8] "5" "6" "5" "6" ...
..@ bamRanges :Formal class 'GRanges' [package "GenomicRanges"] with 7 slots
.. .. ..@ seqnames :Formal class 'Rle' [package "IRanges"] with 5 slots
.. ..@ values : Factor w/ 1 level "Scchr13": 1
.. ..@ lengths : int 27
.. ..@ elementMetadata: NULL
.. ..@ elementType : chr "ANY"
.. ..@ metadata : list()
.. .. ..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
.. ..@ start : int [1:27] 798517 801771 804455 808999 810465 811088 818826 820255
822762 832338 ...
.. ..@ width : int [1:27] 2862 933 636 234 114 108 1122 2199 1869 915 ...
.. ..@ NAMES : NULL
.. ..@ elementMetadata: NULL
.. ..@ elementType : chr "integer"
.. ..@ metadata : list()
.. .. ..@ strand :Formal class 'Rle' [package "IRanges"] with 5 slots
.. ..@ values : Factor w/ 3 levels "+","-","*": 1
.. ..@ lengths : int 27
.. ..@ elementMetadata: NULL
.. ..@ elementType : chr "ANY"

.. ..@ metadata : list()
.. .. ..@ seqlengths : Named int NA
.. ..- attr(*, "names")= chr "Scchr13"
.. .. ..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
.. ..@ rownames : NULL
.. ..@ nrows : int 27
.. ..@ elementMetadata: NULL
.. ..@ elementType : chr "ANY"
.. ..@ metadata : list()
.. ..@ listData :List of 1
.. ..$ name: chr [1:27] "YMR266W" "YMR267W" "YMR269W" "YMRWdelta20" ...
.. .. ..@ elementType : chr "ANY"
.. .. ..@ metadata : list()
..@ bamExperiment:List of 1
.. ..$ annotation: chr "org.Sc.sgd.db"

Details

Illumina short reads from a very small segment of yeast chr XIII have been collected

Source

FASTQ data available at ftp://ftp.ncbi.nlm.nih.gov/sra/Studies/SRP000/SRP000632/

References

Albert Lee and Kasper Daniel Hansen and James Bullard and Sandrine Dudoit and Gavin Sherlock, Novel Low Abundance and Transient RNAs in Yeast Revealed by Tiling Microarrays and Ultra High–Throughput Sequencing Are Not Conserved Across Closely Related Yeast Species, PLoS Genet, v4, e1000299, Dec 2008

Examples

```
library(leeBamViews)  # bam files stored in package
bpaths = dir(system.file("bam", package="leeBamViews"), full=TRUE, patt="bam$")
#
# extract genotype and lane information from filenames
#
gt = gsub(".*/", "", bpaths)
gt = gsub("_.*", "", gt)
lane = gsub(".*(.)$", "\\1", gt)
geno = gsub(".$", "", gt)
#
# format the sample-level information appropriately
#
pd = DataFrame(geno=geno, lane=lane, row.names=paste(geno,lane,sep="."))
prd = new("DFrame")  # protocol data could go here
#
# create the views object, adding some arbitrary experiment-level information
#
```

```
bs1 = BamViews(bamPaths=bpaths, bamSamples=pd,
        bamExperiment=list(annotation="org.Sc.sgd.db"))
bs1
# add ranges and tabulate reads

START=c(861250, 863000)
END=c(862750, 864000)
exc = GRanges(IRanges(start=START, end=END), seqnames="Scchr13", strand="+")
values(exc)$name = c("intv1", "intv2")  # necessary
bamRanges(bs1) = exc
bs1
tabulateReads(bs1, "+")
```

---

leeRPKM *supplemental data extract on RNA seq results in yeast*

Description

supplemental data extract on RNA seq results in yeast

Usage

```
data(leeRPKM)
```

Format

A data frame with 6291 observations on the following 16 variables.

`chr` a numeric vector

`strand` a numeric vector

`start` a numeric vector

`end` a numeric vector

`name` a factor with levels `LSR1` `NME1` `YAL001C` `YAL002W` `YAL003W` ...

`feature` a factor with levels `CDS` `CDS_unchar` `snRNA` `snoRNA`

`orf_classification` a factor with levels `Uncharacterized` `Verified` `silenced_gene3AVerified`

`gene` a factor with levels `AAC1` `AAC3` `AAD10` `AAD14` `AAD15` `AAD16` `AAD3` `AAD4` ...

`wt.reads` a numeric vector

`rrp.reads` a numeric vector

`ski.reads` a numeric vector

`xrn.reads` a numeric vector

`wt.rpkm` a numeric vector

`rrp.rpkm` a numeric vector

`ski.rpkm` a numeric vector

`xrn.rpkm` a numeric vector

Source

imported from supplemental data

References

Lee et al PLOS genetics December 2008 ; Volume 4 ; Issue 12 ; e1000299

Examples

```
data(leeRPKM)
leeRPKM[1:5,]
```

`leeUnn` *supplemental data extracts on existing evidence of transcription in yeast*

Description

supplemental data extracts on existing evidence of transcription in yeast

Usage

```
data(leeUnn)
```

Format

A data frame with 54822 observations on the following 11 variables.

`chr` a numeric vector

`start` a numeric vector

`end` a numeric vector

`strand` a numeric vector

`lengthWithoutMask` a numeric vector

`length` a numeric vector

`lambda` a numeric vector

`background5` a logical vector

`background20` a logical vector

`reads` a numeric vector

`study` a factor with levels `David` `Davis` `Miura` `Nagalakshmi`

Source

from Lee et al PLoS genetics December 2008 Volume 4 Issue 12 e1000299 supplemental data

information on unnannotated transcripts for which some evidence of transcription was obtained in this experiment

Examples

```
data(leeUnn)
leeUnn[1:5,]
```

---

tabulateReads *tabulate counts of alignments occurring in specified genomic regions*

Description

tabulate counts of alignments occurring in specified genomic regions

Usage

```
tabulateReads(bv, strandmarker=NULL, as.GRanges=FALSE, applier=lapply)
```

Arguments

bv	BamViews-class instance
strandmarker	character atom: '+' or '-'; if missing, ignore strand
as.GRanges	logical directive to return a GRanges instance instead of a matrix
applier	lapply-like function; if unspecified and multicore is attached will use mclapply

Details

readGAlignments is the basic engine for this task

Value

annotated matrix with start, end, and samples as rows, regions as columns, and read counts as cell entries

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
example(bs1)
#
# counts in a partition
#
myrn = GRanges(IRanges(start=seq(861250, 862750, 100), width=100),
    seqnames="Scchr13", strand="+")

values(myrn)$name = paste("til", 1:length(myrn), sep=".")
bamRanges(bs1) = myrn
tabulateReads(bs1, "+")
#
```

```
# a related computation based on countBam
lapply(bamPaths(bs1)[1:2], function(x)
    countBam(x,  param=ScanBamParam(which=bamRanges(bs1))))
```

`totalReadCounts` *scan BAM files for total read counts*

Description

scan BAM files for total read counts

Usage

```
totalReadCounts(x)
```

Arguments

x	BamViews-class instance

Details

slow procedure – does lightweight scan of entire file

Value

named integer vector of read counts per sample

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
example(bs1)
totalReadCounts(bs1)
```

Index

∗ **datasets**
bs1, 2
leeRPKM, 4
leeUnn, 5
∗ **models**
tabulateReads, 6
totalReadCounts, 7

bs1, 2

leeRPKM, 4
leeUnn, 5

readGAlignments, *6*

tabulateReads, 6
tabulateReads,BamViews,character_OR_NULL,logical,function-method
*(*tabulateReads*)*, 6
tabulateReads,BamViews,character_OR_NULL,missing,missing-method
*(*tabulateReads*)*, 6
tabulateReads,BamViews,missing,missing,missing-method
*(*tabulateReads*)*, 6
totalReadCounts, 7
totalReadCounts,BamViews-method
*(*totalReadCounts*)*, 7